



**Innovation in Intelligent Power**

Tel: 01823 662414 Email: info@pduexpertuk.com

*The most innovative PDU on the market*



**Intelligent, Rack Mounted,  
Power Distribution Units**

## KWY PDU

KWY-N32A48C3-V3W\_Yel  
POPM PER OUTLET POWER METERING



***PDUeX as standard  
where others don't!!***

- ✓ Monitor Each Sockets Current
- ✓ Control each outlets on/off
- ✓ Sequential power on/off
- ✓ User can define the sequence of order in which outlets will be switched on.
- ✓ Wifi enable
- ✓ Monitor the Total Current
- ✓ Monitor the Input Voltage
- ✓ Monitor the total kWh
- ✓ Power Factor Recognition
- ✓ Monitors Input & Output Voltage
- ✓ 48 IEC C13 Lockable outlets
- ✓ 55°C Hot Rack Operating
- ✓ SMS, SNMP, DHCP & Email
- ✓ Notification Built in Environmental Monitoring Technology as Standard
- ✓ Up to 6, Plug 'n' Play Sensors
- ✓ Bade Server Ready
- ✓ Dry Connector for Audible Alarms
- ✓ Intelligent Outlet Type & number Recognition
- ✓ 24V and 48, Single Phase 120V, 230, & 400V

***Innovation in Intelligent Power***

## KWY

### Remote Monitored PDU

KWY series is the new generation of intelligent PDU. It combines network power distribution and environmental monitoring technology; it provides real-time remote power consumption of total current load and voltage. Boot up a single or dual power server by clicking (On/Off). Re-boot server remotely by clicking the reset button in the PDU management software. As well as providing TCP/ IP protocol, KWY provides also Wifi Capability, for Smart phones, tablet computer and other mobile devices access. KWY POPM provides Total Power Monitoring, Outlet Power Switched and Outlet Power Metering. Provides Power information of individual outlet/port includes current, voltage, power (kW), apparent power and power factor. receive SNMP-based email alerts when power or environmental surroundings go above the thresholds. Assign access rights to user groups or individuals. KWY POPM products provide the necessary flexibility with embeded multithreading inner core (RTOS) Real time Operating systems)the software supports multitask and multisuser access. RTOS software supports also various TCP/IP protocols, including HTTP, HTTPS, SNMP, TELNET, SSH, SMTP etc.

### Socket Types



**Vertical mounted (L x W x D)** 1804 x 44.5mm x 44.5mm

A = length can be customized



Items		Description	N1	N2	N3	N4
Monitor Functions	LED Display	Current Load of total pdu and per ports	✓	✓	✓	✓
		LED flashes when overload	✓	✓	✓	✓
		PDU Address, Version Number	✓	✓	✓	✓
	Managing software/Hyper Terminal	Total Current Load	✓	✓	✓	✓
		Monitors Current Load Per Ports	✗	✓	✗	✓
		Input Voltage	✓	✓	✓	✓
		Max. Voltage configured	✓	✓	✓	✓
		Max. Current configured	✓	✓	✓	✓
		Sensors state (optional)	✓	✓	✓	✓
Control Functions	PC Control	On/off of individual unit	✗	✗	✓	✓
		Power On /Off time setting	✗	✗	✓	✓
		Stay the same after restart	✗	✗	✓	✓
Accessing Method		RS 485 port	✓	✓	✓	✓
Daisy-chain ways		Serial and radiation connection	✓	✓	✓	✓



## KWY-N32A24P24C3-V3W


KWY POPM provides:

- 1.Total Power Monitoring,
2. Outlet Power ON / OFF and Outlet Power information of individual outlet/port includes( current, voltage, power (kW), apparent power and power factor)
- 3.Total 11 interfaces (NET & RS232, Cascade, USB, SI 1-6) 4. Auto Power Alarm. Hot-swappable NETWORK Card
- 5- Optional 3Phase Power supply
- 6 Embedded remote management systems, supports various TCP/IP protocols, including: HTTP, SSL, SNMP V1,V2 & V3, TELNET, SSH,SMTP, NTP

**Provides:** Sensors recognition, Ability to cascade up to 4units, Monitor the total current, Monitor the total kWh, and Monitor the input voltage.

**It offers:** Monitor only PDU Power consumption, Switchable, Power factor recognition, Monitor the input voltage, 24 x lockable IEC C13.


**Optional:** Temperature and humidity, Smoke alarm, Water logging alarm, Rack Door alarm



Select	No.	Outlet	Socket	Power	Load	On/Off	Action	Status
<input type="checkbox"/>	1-A1	Outlet_1,1	IEC 320 C13	NORMAL	0.0	ON	Complete	
<input type="checkbox"/>	1-A2	Outlet_1,2	IEC 320 C13	NORMAL	0.0	ON	Complete	
<input type="checkbox"/>	1-A3	Outlet_1,3	IEC 320 C13	NORMAL	0.0	ON	Complete	
<input type="checkbox"/>	1-A4	Outlet_1,4	IEC 320 C13	NORMAL	0.0	ON	Complete	
<input type="checkbox"/>	1-A5	Outlet_1,5	IEC 320 C13	NORMAL	0.0	ON	Complete	
<input type="checkbox"/>	1-A6	Outlet_1,6	IEC 320 C13	NORMAL	0.0	ON	Complete	
<input type="checkbox"/>	1-A7	Outlet_1,7	IEC 320 C13	NORMAL	0.0	ON	Complete	
<input type="checkbox"/>	1-A8	Outlet_1,8	IEC 320 C13	NORMAL	0.0	ON	Complete	
<input type="checkbox"/>	A0							

Address Code 1998A1 PDU Type KWY-N32A24C3-V3W On Interval 1 Second  
 Instantaneous Power 0.0 W Rated Power 3200.0 W Remaining Power 3200.0 W  
 Total load 0.0 A Voltage 230 V Power Factor 0.99  
 Energy 0.0 kWh

### Radiation Connection



## KWY-N32A24P24C3-V3W

Part number	KWY-N32A24P24C3-V3W
Product series	KWY series 3
Product Size	W x D x H = 1804mm x 44.45mm x 44.45
Mounting length	465 mm

Case color	Black
Net Weight	6.5KG
Socket type Output	24 x Lockable IEC-C13
Socket Power Input	IEC-320 C20 32A

Function	Illustration	Parameter	Note
Working voltage	Normal working	AC90~250V	
Input/output current	Max input/output current	16A 10A	
Working band	Under normal working	47~60Hz	
Access	Net port	Via WAN or LAN monitor access	10/100Mb Adaptive Networking
	Serial port	Via Serial port monitor access	RS485 port
	Sensor port	Sensors access	RS485 port
Access way	HTTP/HTTPS	Web browser access	Adapt IE Fire fox inner core browser, support SSL;
	TELNET	Simple command lines access	/
	SSH	Encryption command lines access	Support SSHV2 version
	SNMP	Support SNMP for centralized monitor	Adapt SNMP v1, V2
Operation system compatibility	Support various operation system	Windows/winsta/win7/linux etc.	
Secondary development	Used for system integrate	Opening protocol TELNET SSH	
	RS485	Customized protocol	
Software upgrade	Manage software load	Support manage software upgrade	
	Software on circuit	Support software upgrade on the circuit of hardware	
Alarm limit settings	Total current limit		
	Temperature limit	Auto identify limit rationality	
	Humidity limit		
Display, Indicate	Outlets indicators	Each outlets with a indicator	Optional
	6 digital indicators	Nixie tube show the current/voltage, inquiry products information, Alarm information;	
Menu button operation	Inquiry information	Inquiry product information, Alarm information, current etc.	
	On/off Alarm sound, Dry connect	Close/ open alarm sound and dry connect output, Dry connect have normal open/off two choice, passive, touch spot can connect 2A 250VAC	
Management	User right limit	Administrator, Normal user	
	Outlets grouping	Make group over PDU self sockets limit	
	clock synchronization	Regulate PDU system clock	
Log record	Alarm log	Alarm log circle, Inquiry, export, stock, delete available	

Control	Control each outlets on/off	Each outlet breaking capacity 16A 250VAC	Optional
	Sequential power on/off	The interval of sequential power off time: 0.5s, Sequential power on 1~250s, user-defined	
	Power status holding	When PDU restart power, Each outlets will remain the status before	
Monitor	Manage software load	Support manage software upgrade	
	Monitor the input voltage	Resolution:1V Accuracy: $\pm 1\%+1$ digit Meter range: 90~350V	
	Monitor the total current	Resolution: 0.1A Accuracy: $\pm 1\%+1$ digit Meter range: 0.1~40A	
	Monitor the total kWh	Resolution: 0.1KW-H Accuracy: 1 grade	
	Monitor Environment Temperature	Resolution: 1 Accuracy: $\pm 1\%+1$ digit Meter range: -30~100	Optional
	Monitor Environment Humidity	Resolution: 1% Accuracy: $\pm 1\%+1$ digit Meter range: 01~99%	Optional
	Monitor Environment Smoke	Max: 25 m <sup>2</sup> available	Optional
	Monitor water logging	Water logging or drop monitor	Optional
	Infrared monitoring	The max monitor distance: 16m	Optional
	Door open monitor	Min. 5mm open distance available	Optional
	Surge protection failure monitor	PDU still normal working when failure	Optional
Outlets alarm settings	Each fuse failure alarm		Optional
	Total current over limit alarm	PS/PN series local alarm ways: PDU buzzer alarm, sound and light alarm, Dry connect; PN series remote alarm: E-mail, SMS, SNMP TRAP, WEB page notice, TELNET/SSH notice	
	Temperature over limit alarm		Optional
	Humidity over limit alarm		Optional
	Smoke Alarm		Optional
	Water logging alarm		Optional
	Infrared enter alarm		Optional
	Door open alarm	KWX-N series remote alarm: E-mail, SMS, SNMP TRAP, WEB page notice,	Optional
	Surge protection failure alarm		Optional
Protection	Surge protection	Difference mode: $\pm 2kV$ Common mode $\pm 2KV$ flux: 3KA The max discharge current: 5KA	Optional
	Each way with fuse	Breaking capacity : 1500A; Protect main line break, facility, power line suffering, Fuse range: 0.1~16A	Optional
	Circuit Breaker protection	Breaking capacity : 6000A	Optional
	Recoverable overload protector	Overload protection	Optional
Intelligent recognition	Outlets recognition	Automatic read the sockets type and numbers	
	Sensors recognition	Sensors port no need be defined, Automatic read the sensors type and numbers	
	Limit recognition	When over limit, setting failure	
	The MAX output current and PDU power	Help user to limit facilities connect number and type	
	Power factor recognition	Help user to know the current consuming apparatus	
Sensors in	1 ~ 8pcs same or different sensors connect in one PDU	Flexible sensor input, extend and choose, Customized for new sensors	Optional
Cascade chain	KWX-N with KWX-N Cascade	Directly connection via net cable; Via HUB 4 sets Cascade at most	
	KWX-N with KWX-S Cascade	Directly connection via net cable, 4 sets Cascade at most	



## KWX Model Numbers

Please specify series by character highlighted in **red** and your model type in **green**  
eg: KWX-**N**16A10C3-H**1F**



KWX-**N/S**16A8C3-H**1/2/3/4F**



KWX-**N/S**16A10C3-**1/2/3/4**



KWX-**N/S**16A8Schuko-**1/2/3/4**



KWX-**N/S**16A12C3-**1/2/3/4**



KWX-**N/S**16A12C3C94-**1/2/3/4**



KWX-**N/S**16A20C3C94-**1/2/3/4**

### Bespoke Requests Custom build options

With our UK manufacturing capability PDUeX can build to your specifications with our market leading 2 week turn round, including:

- ✓ Surge Protection and SMS SNMP Email Alarm
- ✓ Individually Fused Outlets
- ✓ Recoverable Overload protection
- ✓ Socket types & number
- ✓ 1u/2u Up to 72 outlets
- ✓ Modbus RS485

**Please contact the PDUeX team for assistance:**

Tel: **01823 662414**

or email: [info@pduexpertuk.com](mailto:info@pduexpertuk.com)

## KWX PDU SENSORS



**Infrared Sensor**



**Door Sensor**



**Temperature/  
Humidity Sensor**



**Smoke Sensor**



**Water Logging  
Sensor**