

## PDUeX-SW-32A-08H



### PDUeX-SW-32A-08H - 32A Rack mountable Intelligent 8 Port Switched Horizontal Power Distribution Unit

*PDUeX Switched PDU series give the necessary flexibility that allows Datacentre Managers to remotely control and monitor PDU's. Remote outlet level controls allow power on/off functionality for power recycling and restart secured IT equipment and to avert wrongfully use of individual outlets. Current-meter (True RMS) that shows the total power consumption of the PDU and provides real-time remote monitoring of connected servers. Power sequencing defined, allowing users to specify the structure in which to power On/Off any connected equipment. User-Defined Alarm, thresholds for Warning of potential circuit overloads before significant IT hitch appear. Users can access, configure, and control PDUeX-SW-32A-08H PDUs through secure Web, SNMP Interfaces and comes with PDUeX PDU Management software that allows IT Manager to control multiple PDU.*

### “Quality Manufactured PDU's to British & EU Standards”

- ✓ Remote outlet level controls allow power on/off functionality for power recycling and restart locked-up IT equipment.
- ✓ Current-meter (True RMS) that shows the total power consumption of the PDU and provides real-time remote monitoring of connected servers.
- ✓ Power sequencing defined, allowing users to specify the structure in which to power On/Off any connected equipment.
- ✓ User-Defined Alarm, thresholds for Warning of potential circuit overloads before significant IT hitch appear.
- ✓ Users can access, configure, and control PDUeX-SW-32A-08H PDUs through secure Web, SNMP Interfaces and comes with PDUeX PDU Management software that allow IT Manager to control multiple PDU.
- ✓ Available in 16 & 32 Amp, 2,8,16,24 outlets



Customer note: Due to continual improvements in design or otherwise, this product may differ slightly from the illustration(s).

## PDUeX-SW-32A-08H Features & Specifications

Features	Current meter	Digital true RMS current meter
	Power monitor	Remote total power monitoring by meter
	Monitor	Web, SNMP, Free bundle software
	Protocols	Http, Https, SNMP, DHCP, UDP
	Outlet control	Individual outlet control
	Power delay	Power ON/OFF sequence can be defined
	Alarm thresholds	User-defined alarm thresholds for warning
General Specification	Output	8x IEC320 C13
	Input	IEC320 C20 inlet; Enclosed IEC320 C19 to C20 3 meter power cord
Communication	SSL indication	1x Yellow LED
	DHCP indication	1x Green LED
	Output status	8x Red LED
	Network	1x RJ45 for Ethernet
	Current meter	3 Digit/7 segment reader for True RMS meter <ul style="list-style-type: none"> <li>➤ Range 0A ~ 20A</li> <li>➤ Resolution: 0.1A</li> <li>➤ Precision <math>\pm 2\%</math> / <math>\pm 0.1A</math></li> </ul>
Operation	Nominal voltage	230V
	Voltage	200V ~ 240V full range
	Frequency	50/60HZ full range
	Max output current	16A
	Temperature	0c° ~ 40c°
	Humidity	0% ~ 90%
	Size	440mm x 44mm x 950mm
Weight	2kg	
Regulatory Approvals	CE, EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3 C-Tick AS/NZS CISPR 22: 2006 FCC Part 15 Class A, ICES-003	



Hardwired to 3m tri core 4mm lead with 32A Commando

## Effortless Management software

PDUeX SW series comes complete with a simple to use interface, giving Data center managers easy access to the PDU to monitor and control each outlet. The PDUeX interface can be accessed directly via Ethernet cable or via a network (HTTP, HTTPS, DHCP, SNMP & UDP).

Features include:

- Monitor multiple PDUs
- Set alarm thresholds
- Configure event alerts

